



The ideal power for turboprop aircraft

H-Series is a family of turboprop engines by Avio Aero - part of GE Aerospace - offering a customized range of ratings and performance for commuters, private as well as multi-purpose aircraft. From skydiving to medical support and cargo transport, the engine thrives in rugged conditions that require mission readiness, short takeoffs, weight variability and safe operation: in the hottest deserts, over the highest peaks and across the most remote archipelagos, H-Series is renowned for its reliability.

Its standard configuration allows a seamless, lowinvestment integration into a variety of airframe types. The H-Series is a two-shaft, reverse flow engine with a free turbine. The engine has an axial compressor and compressor turbine featuring 3D geometry design. Fuel is distributed to the chamber via the slinger ring combustor architecture, which simplifies maintenance and eliminates the need for recurrent fuel nozzle inspections. The propulsion section is powered by a single-stage turbine driving a two-stage planetary gearbox.

Electronic Controls

The H-Series engine is available with new, first-in-class Electronic Engine and Propeller Control (EEPC). The EEPC system, featuring fully integrated engine and propeller operations, provides safer operations.

An Aerobatic version of H-Series engine, with a unique multi attitude lubrication system designed to enable flight with zero gravity and strengthened structure for demanding aerobatic maneuvers is undergoing final development tests.





Engine features

- · A legacy of 21+ million fight hours
- · Low maintenance operations
- No hot section inspection and no fuel nozzles required
- Reliable performance in harsh environments
- · Optimized aero design and features for reduced SFC
- Modern, proven GE Aerospace materials for longer life

Optional services


- Prepaid Maintenance Program available
- Remote diagnostics and special mission accessories including Vibration Monitoring System (for all Aerobatic models)

Specifications (sea level, standard day)

Thermodynamic power (THP)	1040
Propeller speed	2080 or 1950
Propeller rotation	CW from rear
Maximum operating envelope (depending on installation)	Up to 32000 ft
Basics TBO interval	Up to 4000 hours
HSI interval/fuel nozzle inspection	None
Control system	Hydro mechanical fuelcontrol or Electronic Engineand Propeller Control
Fuel	Jet A, Jet A1, SAF
Weight (basic dry mass)	177 kg (390 lb)
Dimensions (I, w, h)	1670 mm (66"), 560mm (22"), 580 mm(23")

Engine models

H75 550 or 750 SHP



Sea level10,000 ft

H80 800 SHP



H85 850 SHP





© 2023 Avio Aero - All rights reserved.

Avio Aero reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your Avio Aero representative for the most current information.